

# SHARP QT-CD180H (S)/(BL)/(RD)/(WH) NEW PRODUCT PREVIEW

Portable CD Stereo System

For internal use only



QT-CD180H (S)



QT-CD180H (BL)



QT-CD180H (RD)



QT-CD180H (WH)

Product appearance is subject to change.

## Compact and Stylish Portable CD Stereo System with Cassette Deck

- Compact and Stylish Design
- Built-in CD Player
- Built-in Cassette Deck
- X-BASS (EXTRA BASS) System
- LCD Display for CD
- CD Pause
- 2-Band (FM Stereo/AM) Tuner
- APSS (Auto Program Search System) for CD

### Specifications (tentative)

Power source	AC 230 – 240 V/50 Hz, DC 9 V (UM/SUM-1 or R20 x 6)
Power output	MPO: 8.4 W (4.2 W + 4.2 W) (AC operation, DIN 45 324) RMS: 4.6 W (2.3 W + 2.3 W) (European Continent: DC operation, DIN 45 324) (UK: DC operation, 10% T.H.D.)
Frequency range	FM: 87.5 – 108 MHz, AM: 526.5 – 1,606.5 kHz
Terminals	AC input socket
Dimensions	376 (W) x 150 (H) x 230 (D) mm
Weight	Approx. 2.5 kg

Design and specifications are current as of January 2001, but are subject to change without prior notice.  
\* Audio-visual material may consist of copyrighted works which must not be recorded without the authority of the owner of the copyright. Please refer to relevant law in your country.



# QT-CD180H (S)/(BL)/(RD)/(WH) *Sistema estéreo portátil con reproductor de CD*

## ***Sistema estéreo portátil con reproductor de CD, compacto y elegante, con grabadora de cassette***

- **Diseño compacto y elegante**
- **Reproductor de discos compactos incorporado**
- **Grabadora de cassette incorporada**
- **Sistema X-BASS (extragraves)**
- Pantalla LCD para discos compactos
- Pausa de CD
- Sintonizador de 2 bandas (FM en estéreo/AM)
- APSS (Sistema de búsqueda de programa automático) para discos compactos

### ***Especificaciones (provisionales)***

Fuente de alimentación	230 – 240 V CA/50 Hz, CC de 9 V (UM/SUM-1 o R20 x 6)
Potencia de salida	Musical (MPO): 8,4 W (4,2 W + 4,2 W) (Funcionamiento a CA, DIN 45 324) RMS: 4,6 W (2,3 W + 2,3 W) (Continente Europeo: Funcionamiento a CC, DIN 45 324) (Reino Unido: Funcionamiento a CC, 10% de D.A.T.)
Gama de frecuencias	FM: 87,5 – 108 MHz AM: 526,5 – 1.606,5 kHz
Terminales	Toma de entrada de CA
Dimensiones	376 (An.) x 150 (Al.) x 230 (Prof.) mm
Peso	Aprox. 2,5 kg

Diseño y especificaciones vigentes en enero de 2001, pero sujetas a cambios sin previo aviso.

\* El material audiovisual puede incluir obras protegidas por leyes sobre derechos de autor que no deben ser grabadas sin el consentimiento del dueño de los derechos de autor. Consulte las leyes de su país al respecto.