

185 WATT

**BIG POWER,
SMALL FOOTPRINT**



FEATURES

- High-power module (185W) using 155.55mm square single crystal silicon solar cells with 14.1% module conversion efficiency
- Photovoltaic module with bypass diode minimises the power drop caused by shade
- Textured cell surface to reduce the reflection of sunlight and BSF (Back Surface Field) structure to improve cell conversion efficiency: 15.9%
- White tempered glass, EVA resin and a weatherproof film, plus aluminum frame for extended outdoor use
- Output terminal: Lead wire with waterproof connector
- Certifications: IEC 61215 & IEC 61730
- SHARP modules are manufactured in ISO 9001 certified factories

SINGLE CRYSTAL SILICON PHOTOVOLTAIC MODULE WITH 185W MAXIMUM POWER

This single crystal 185watt module features 15.9% encapsulated cell efficiency and 14.1% module efficiency. Using breakthrough technology perfected in Sharp's space cell program, the **NU-S5E3E** module allows for maximum usable power per square metre of solar array.

A safe, clean, reliable source of energy, Sharp's NU-S5E3E photovoltaic module is designed for large electrical power requirements. Based on the technology of crystal silicon solar cells developed over 50 years, this module has superb durability to withstand rigorous operating conditions and is suitable for grid connected systems.

Common applications for the Sharp NU-S5E3E include residences, office buildings, solar power stations and solar suburbs. As one of the world's leading manufacturer of photovoltaic modules, Sharp produces an extensive line of high power modules for every electrical power requirement.

SHARP

NU-S5E3E – MAXIMUM POWER

ELECTRICAL CHARACTERISTICS

Cell	48 Monocrystalline (155.55mm) ² Sharp silicon solar cells
No. of Cells and Connections	48 in series
Open Circuit Voltage (Voc)	30.2V
Maximum Power Voltage (Vpm)	24V
Short Circuit Current (Isc)	8.54A
Maximum Power Current (Ipm)	7.71A
Maximum Power (Pm) ¹	Typical 185W
Encapsulated Solar Cell Efficiency (ηc)	15.9%
Module Efficiency (ηm)	14.1%
Maximum System Voltage	DC 1000V
Series Fuse Rating	15A
Type of Output Terminal	Lead Wire with MC3 Connector

¹ (STC) Standard Test Conditions: 25°C, 1 kW/m², AM 1.5

MECHANICAL CHARACTERISTICS

Dimensions	1318 x 994 x 46mm
Weight	16.0kg




TEMPERATURE COEFFICIENT

Temp. Coefficient of Pmax	-0.485	% / °C
Temp. Coefficient of Voc	-0.104	V / °C
Temp. Coefficient of Isc	0.053	% / °C




ABSOLUTE MAXIMUM RATINGS

Parameters	Rating	Unit
Operating Temperature	-40 to +90	°C
Storage Temperature	-40 to +90	°C
Dielectric Voltage Withstood	3000 max.	V-DC

IV CURVES



DIMENSIONS



In the absence of confirmation by device specifications sheets, Sharp takes no responsibility for any defects that may occur in equipment using any Sharp devices shown in catalogues, data books, etc. Contact Sharp in order to obtain the latest device specification sheets before using any Sharp device.

- Design and specifications are subject to change without prior notice.
- Colour variations to products may occur due to printing.
- All information and technical details are correct as at product release date.

SHARP

SHARP CORPORATION OF AUSTRALIA PTY LTD
 ABN 40 003 039 405
 1 Huntingwood Drive, Huntingwood, NSW 2148
 PO Box 6827, Blacktown, NSW 2148
 Tel: (02) 9830 4600 Fax: (02) 9672 1208
 www.sharp.net.au

SHARP

Solar

